



## WAYPOINTS COORDINATES

WPT	COORD
CH701	402912.6N 0000154.2W
CH702	403007.8N 0000607.7E
CH703	402847.0N 0001403.3E
CH704	402713.3N 0001748.2E
CH705	402451.5N 0002302.2E
CH706	400933.5N 0002702.4E
CH707	401452.3N 0002725.9E
CH708	401855.0N 0002614.1E
CH709	402322.6N 0002432.4E
OSPES (IAF)	402221.2N 0002049.0E
RIMES	403328.6N 0000350.2W
SOPET	395001.8N 0000016.9W
TORDU	401528.5N 0003517.5E

## STANDARD INSTRUMENT ARRIVALS (STAR) RUNWAY 24

### NOTES APPLICABLE TO ALL STAR:

- RNAV1.
- SPEED CONTROL:
  - MAX IAS 250 kt at FL120 or below.

## PROCEDURE TABULAR DESCRIPTION

RIMES1X												
GNSS required.												
Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track (°T)	°M	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navigation specification
001	IF	RIMES	-	-		-1.5	-	-	+FL100	-	-	RNAV 1
002	TF	CH701	-	159 (160.9)		-1.5	4.5	-	-	-	-	RNAV 1
003	TF	CH702	-	080 (081.4)		-1.5	6.2	-	-	-	-	RNAV 1
004	TF	CH703	-	101 (102.5)		-1.5	6.2	-	+FL075	-	-	RNAV 1
005	TF	CH704	-	117 (118.6)		-1.5	3.3	-	-	-	-	RNAV 1
006	TF	CH705	-	119 (120.6)		-1.5	4.6	-	-	-	-	RNAV 1
007	TF	OSPES	-	213 (214.1)		-1.5	3.0	-	+5000	-	-	RNAV 1

SOPET1X												
GNSS or (DME/DME/IRU) required.												
Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track (°T)	°M	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navigation specification
001	IF	SOPET	-	-		-1.5	-	-	+FL100	-	-	RNAV 1
002	TF	CH706	-	045 (047.0)		-1.5	28.7	-	-	-	-	RNAV 1
003	TF	CH707	-	002 (003.2)		-1.5	5.3	-	-	-	-	RNAV 1

## SOPET1X

GNSS or (DME/DME/IRU) required.

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track (°T)	°M	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navigation specification
004	TF	CH708	-	346 (347.2)		-1.5	4.1	-	-	-	-	RNAV 1
005	TF	CH709	-	342 (343.8)		-1.5	4.6	-	-	-	-	RNAV 1
006	TF	OSPES	-	249 (250.3)		-1.5	3.0	-	+5000	-	-	RNAV 1

## TORDU1X

GNSS or (DME/DME/IRU) required.

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track (°T)	°M	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navigation specification
001	IF	TORDU	-	-		-1.5	-	-	+FL100	-	-	RNAV 1
002	TF	CH707	-	263 (264.3)		-1.5	6.0	-	-	-	-	RNAV 1
003	TF	CH708	-	346 (347.2)		-1.5	4.1	-	-	-	-	RNAV 1
004	TF	CH709	-	342 (343.8)		-1.5	4.6	-	-	-	-	RNAV 1
005	TF	OSPES	-	249 (250.3)		-1.5	3.0	-	+5000	-	-	RNAV 1

## HOLDING PATTERN

Path terminator	Waypoint identifier	Fly-over	Course/Track (°T)	°M	Magnetic variation	Distance/ time	Outbound	Turn direction	MNM altitude (ft)	MAX altitude (ft)	Speed (kt)	Navigation specification
HM	OSPES (1)	-	231 (232.0)		-1.5	4.6 NM		L	+5000	-	-	RNAV1

## REMARKS

(1) GNSS required.