

ALMERIA
ILS Z
RWY 25



①HOLDING MAX LEVEL SUBJECT TO LED168 ACTIVITY.



REQUISITOS DE LA BASE DE DATOS AERONÁUTICA

AERONAUTICAL DATABASE REQUIREMENTS

PROCEDIMIENTOS DE APROXIMACIÓN POR INSTRUMENTOS
INSTRUMENT APPROACH PROCEDURES

ILS Z RWY 25

PUNTO	LAT	LONG	AZIMUT VERDADERO	DME DISTANCE (NM)
POINT	LAT	LONG	TRUE BEARING	DME DISTANCE (NM)
NIDON (IAF)	370500.5N	0020535.6W	028.00° (AMR)	17.00 DME AMR
RIXAL (IAF)	364704.1N	0020104.2W	104.00° (AMR)	12.00 DME AMR
MAXET (IAF)	363257.8N	0021533.9W	180.00° (AMR)	17.00 DME AMR
IF	365457.7N	0020428.7W	073.00° (LOC IAM)	14.00 DME ILS
FAP	365311.6N	0021145.0W	073.00° (LOC IAM)	7.91 DME ILS
Aproximación final de precisión - Pendiente (Ángulo de descenso) Precision final approach - Slope (Descent angle)				5.24% (3.00°)