


ALMERIA
LOC
RWY 25



CAMBIOS:
CHANGES:

REQUISITOS DE LA BASE DE DATOS AERONÁUTICA

AERONAUTICAL DATABASE REQUIREMENTS

PROCEDIMIENTOS DE APROXIMACIÓN POR INSTRUMENTOS
INSTRUMENT APPROACH PROCEDURES

LOC RWY 25

PUNTO	LAT	LONG	AZIMUT VERDADERO	DME DISTANCE (NM)
POINT	LAT	LONG	TRUE BEARING	DME DISTANCE (NM)
L AM (IAF)	365233.0N	0021423.6W	-	-
NIDON (IAF)	370500.5N	0020535.6W	028.00° (AMR)	17.00 DME AMR
RIXAL (IAF)	364704.1N	0020104.2W	104.00° (AMR)	12.00 DME AMR
MAXET (IAF)	363257.8N	0021533.9W	180.00° (AMR)	17.00 DME AMR
IF	365457.7N	0020428.7W	073.00° (LOC IAM)	14.00 DME ILS
FAF	365317.8N	0021119.7W	073.00° (LOC IAM)	8.26 DME ILS
MAPT	365110.9N	0021959.1W	073.00° (LOC IAM)	1.00 DME ILS
Aproximación final de precisión - Pendiente (Ángulo de descenso) Precision final approach - Slope (Descent angle)				5.24% (3.00°)