



GS	kt	80	100	120	140	160	180
FAF-THR:	mins						
FAF-MAPT: 5.1	mins	3:50	3:04	2:33	2:11	1:55	1:42
ROD: 5.2 %	f/min	424	530	636	742	848	954

ALT/HGT DME (AOG) FNA												
13	12	11	10	9	8	7	6	5	4	3	2	1
							1/10	1390	1070	760	440	

REQUISITOS DE LA BASE DE DATOS AERONÁUTICA

AERONAUTICAL DATABASE REQUIREMENTS

PROCEDIMIENTOS DE APROXIMACIÓN POR INSTRUMENTOS
INSTRUMENT APPROACH PROCEDURES

LOC Z RWY 10

PUNTO	LAT	LONG	AZIMUT VERDADERO	DISTANCIA DME (NM)
POINT	LAT	LONG	TRUE BEARING	DME DISTANCE (NM)
KEMAO (IAF)	363954.2N	0063318.1W	276.91° (IAOG) 275.97° (AOG)	10.00 DME AOG
FAF	363932.4N	0062930.3W	276.91° (IAOG)	6.92 DME AOG
MAPT	363855.7N	0062311.1W	276.91° (IAOG)	1.80 DME AOG
Aproximación final de no precisión - Ángulo de descenso (Pendiente) Non-precision final approach - Descent angle (Slope)				-