




GS	kt	80	100	120	140	160	180
FAP-THR: 3.0 NM	min/s	2:16	1:49	1:31	1:18	1:08	1:01
FAF-MAPT:	min/s						
ROD: 5.2 %	ft/min	425	531	637	743	849	955

ALT/HGT DME (ILS) FNA												
13	12	11	10	9	8	7	6	5	4	3	2	1
										2200 (1030)	1870 (700)	1550 (380)



AERONAUTICAL DATABASE REQUIREMENTS

INSTRUMENT APPROACH PROCEDURES
ILS Z RWY 17

WAYPOINTS COORDINATES

WAYPOINT	COORD
LEZUN (IAF)	430100.0N 0083546.3W
OKOVO (IAF)	430352.6N 0081951.4W
REZAK (IAF)	430735.3N 0082933.4W
ST07N (IF)	430145.2N 0082735.2W
ST600	424750.8N 0082255.4W
ST601	424624.3N 0083049.9W

POINT	LAT	LONG	TRUE BEARING	DISTANCE DME (NM)
ST07N (IF)	430145.2N	0082735.2W	346.16° (LOC IGO)	7.32 DME ILS
FAP	425735.2N	0082611.1W	346.16° (LOC IGO)	3.03 DME ILS
Precision final approach - Slope (Descent angle)				5.24% (3.00°)

NOTES APPLICABLE TO INITIAL SEGMENTS AND MISSED APCH:

- GNSS required.

PROCEDURE TABULAR DESCRIPTION

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navegation specification
LEZUN (IAF)											
001	IF	LEZUN	-	-	+1.0	-	-	+4000	-220	-	RNAV1
002	TF	ST07N	-	084 (082.8)	+1.0	6.1	-	+2600	-	-	RNAV1
MISSED APCH											
001	CF	ST600	-	167 (166.1)	+1.0	-	-	-	-	-	RNAV1
002	TF	ST601	-	257 (256.2)	+1.0	6.0	R	-	-200	-	RNAV1
003	TF	LEZUN	-	347 (346.1)	+1.0	15.0	-	+4000	-220	-	RNAV1

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navegation specification
OKOVO (IAF)											
001	IF	OKOVO	-	-	+1.0	-	-	+4000	-220	-	RNAV1
002	TF	ST07N	-	251 (249.5)	+1.0	6.1	-	+2600	-	-	RNAV1
MISSED APCH											
001	CF	ST600	-	167 (166.1)	+1.0	-	-	-	-	-	RNAV1
002	TF	ST601	-	257 (256.2)	+1.0	6.0	R	-	-200	-	RNAV1
003	TF	LEZUN	-	347 (346.1)	+1.0	15.0	-	+4000	-220	-	RNAV1

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navegation specification
REZAK (IAF)											
001	IF	REZAK	-	-	+1.0	-	-	+4000	-220	-	RNAV1
002	TF	ST07N	-	167 (166.1)	+1.0	6.0	-	+2600	-	-	RNAV1
MISSED APCH											
001	CF	ST600	-	167 (166.1)	+1.0	-	-	-	-	-	RNAV1
002	TF	ST601	-	257 (256.2)	+1.0	6.0	R	-	-200	-	RNAV1
003	TF	LEZUN	-	347 (346.1)	+1.0	15.0	-	+4000	-220	-	RNAV1

HOLDING PATTERN

Path terminator	Waypoint identifier	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	MNM altitude (ft)	MAX altitude (ft)	Speed (kt)	Navigation specification
HM	LEZUN (1)	084 (082.8)	+1.0	4.2	R	4000	-	-230	RNAV1
HM	OKOVO (1)	251 (249.5)	+1.0	4.2	L	4000	-	-230	RNAV1
HM	REZAK (2)	167 (166.1)	+1.0	4.2	R	4000	-	-230	RNAV1

(1) GNSS or (DME/DME/IRU);
- DME LRA, STG must be operational (DME/DME/IRU).
(2) GNSS OR (DME/DME);
- DME LRA, STG must be operational (DME/DME).