

GRAN CANARIA
LOC Y
RWY 03L



AERONAUTICAL DATABASE REQUIREMENTS

INSTRUMENT APPROACH PROCEDURES

LOC Y RWY 03L

WAYPOINTS COORDINATES

WPT	COORD
ADOKI	274355.9N 0152546.4W
BAFEM	274951.6N 0150909.0W
COCTO	274742.2N 0151247.0W
DRANO	273920.4N 0153024.4W
ENETA (IAF)	275529.6N 0145938.4W
FALPU (IF)	274643.8N 0152714.9W
NINGU	275912.9N 0150310.6W
LACOR	273803.7N 0150900.1W
LALTO (IAF)	274153.2N 0150014.3W
LIFBI	274542.0N 0151609.1W
LP415	274725.7N 0151923.5W
LP430	280055.2N 0152059.1W
LPC (IAF)	274942.7N 0152556.1W
NIDES	274016.0N 0151517.2W
SUFEM	280255.9N 0150642.7W
TISCA	274228.1N 0152134.7W
TOMOS (IAF)	273251.0N 0153311.7W

POINT	LAT	LONG	TRUE BEARING	DME DISTANCE (NM)
IF	274643.8N	0152714.9W	201.45° (LOC ILP)	9.00 DME ILS
FAF	275123.9N	0152511.4W	201.45° (LOC ILP)	4.00 DME ILS
MAPt	275434.3N	0152347.3W	201.45° (LOC ILP)	0.60 DME ILS
Non-precision final approach - Slope (Descent angle)				5.65% (3.23°)

CRITICAL DME

FACILITY (ID)	FREQ/CH	COORD
GRAN CANARIA (GDV)	112.90 MHz CH 76X	280437.6297N 0152542.8144W
GRAN CANARIA SUR (LPC)	115.00 MHz CH 97X	274943.2149N 0152555.9428W

NOTES APPLICABLE TO ALL APPROACHES:

- Initial segments, missed apch and holdings: RNAV1.
- GNSS required.
- Subject to GCD51 activity
- Speed control:
 - a. MAX IAS 250 kt to FL100 or below, except military flights on operational or air defence missions or when the operational characteristics do not allow for it.
 - b. If any different instructions are not received by ATC cross:

- TOMOS, ENETA, BAFEM and LALTO at 220 kt,
 - LPC at 210 kt,
 - TISCA at 210 kt,
 - 9.0 DME ILS at IAS 190 kt, and
 - 4.0 DME ILS at IAS 160 kt.
- c. In the event of being unable to comply with it (b), notify it to ATC at the first communication.

PROCEDURE TABULAR DESCRIPTION

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navegation specification
ENETA (IAF)											
001	IF	ENETA	-	-	+3.5	-	-	+5000 (1)	-220	-	RNAV1
002	TF	BAFEM	-	240 (236.3)	+3.5	10.1	-	-	-	-	RNAV1
003	TF	COCTO	-	240 (236.3)	+3.5	3.9	-	-	-	-	RNAV1
004	TF	LIFBI	-	240 (236.2)	+3.5	3.6	-	-	-	-	RNAV1
005	TF	TISCA	-	240 (236.2)	+3.5	5.8	-	-	-210	-	RNAV1
006	TF	ADOKI	-	295 (291.4)	+3.5	4.0	-	-	-	-	RNAV1
007	TF	FALPU	-	338 (334.9)	+3.5	3.1	-	+2500	-190	-	RNAV1
MISSED APCH											
001	CF	LP430	Y	025 (021.4)	+3.5	-	-	-	-	-	RNAV1
002	DF	SUFEM	-	-	+3.5	-	R	@3000	-210	-	RNAV1
003	TF	NINGU	-	143 (139.8)	+3.5	4.9	-	-	-	-	RNAV1
004	TF	ENETA	-	143 (139.8)	+3.5	4.9	-	@4000	-220	-	RNAV1
(1) Minimum altitude 4000 ft under ATC clearance and missed approach.											

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navegation specification
LALTO (IAF)											
001	IF	LALTO	-	-	+3.5	-	-	+5000	-220	-	RNAV1
002	TF	LACOR	-	247 (243.9)	+3.5	8.7	-	-	-	-	RNAV1
003	TF	NIDES	-	295 (291.5)	+3.5	6.0	-	-	-	-	RNAV1
004	TF	TISCA	-	295 (291.5)	+3.5	6.0	-	-	-210	-	RNAV1
005	TF	ADOKI	-	295 (291.4)	+3.5	4.0	-	-	-	-	RNAV1
006	TF	FALPU	-	338 (334.9)	+3.5	3.1	-	+2500	-190	-	RNAV1
MISSED APCH											
001	CF	LP430	Y	025 (021.4)	+3.5	-	-	-	-	-	RNAV1
002	DF	SUFEM	-	-	+3.5	-	R	@3000	-210	-	RNAV1
003	TF	NINGU	-	143 (139.8)	+3.5	4.9	-	-	-	-	RNAV1
004	TF	ENETA	-	143 (139.8)	+3.5	4.9	-	@4000	-220	-	RNAV1

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navegation specification
LPC (IAF)											
001	IF	LPC	-	-	+3.5	-	-	+FL075	-210	-	RNAV1
002	TF	LP415	-	115 (111.4)	+3.5	6.2	-	+6000	-	-	RNAV1
003	TF	TISCA	-	205 (201.4)	+3.5	5.3	-	-	-	-	RNAV1
004	TF	ADOKI	-	295 (291.4)	+3.5	4.0	-	-	-	-	RNAV1
005	TF	FALPU	-	338 (334.9)	+3.5	3.1	-	+2500	-190	-	RNAV1
MISSED APCH											

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navegation specification
001	CF	LP430	Y	025 (021.4)	+3.5	-	-	-	-	-	RNAV1
002	DF	SUFEM	-	-	+3.5	-	R	@3000	-210	-	RNAV1
003	TF	NINGU	-	143 (139.8)	+3.5	4.9	-	-	-	-	RNAV1
004	TF	ENETA	-	143 (139.8)	+3.5	4.9	-	@4000	-220	-	RNAV1

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navegation specification
TOMOS (IAF)											
001	IF	TOMOS	-	-	+3.5	-	-	+5000	-220	-	RNAV1
002	TF	DRANO	-	024 (020.9)	+3.5	6.9	-	-	-	-	RNAV1
003	TF	FALPU	-	024 (020.8)	+3.5	7.9	-	+2500	-190	-	RNAV1
MISSED APCH											
001	CF	LP430	Y	025 (021.4)	+3.5	-	-	-	-	-	RNAV1
002	DF	SUFEM	-	-	+3.5	-	R	@3000	-210	-	RNAV1
003	TF	NINGU	-	143 (139.8)	+3.5	4.9	-	-	-	-	RNAV1
004	TF	ENETA	-	143 (139.8)	+3.5	4.9	-	@4000	-220	-	RNAV1

HOLDING PATTERN

Path terminator	Waypoint identifier	Course/Track °M (°T)	Magnetic variation	Distance/ Outbound time	Turn direction	MNM altitude (ft)	MAX altitude (ft)	Speed (kt)	Navigation specification
HM	ENETA (1)	260 (256.4)	+3.5	1	R	5000 (2)	-	-220	RNAV1
HM	LALTO (3)	230 (226.4)	+3.5	1	L	5000	-	-220	RNAV1
HM	LPC (4)	024 (020.9)	+3.5	1	R	FL075	-	-210	RNAV1
HM	TOMOS (5)	117 (114.0)	+3.5	1	L	5000	FL070	-220	RNAV1
(1) GNSS or (DME/DME) or (DME/DME/IRU) required; - DME LPC, GDV must be operational for (DME/DME). - DME LPC must be operational for (DME/DME/IRU) (2) Minimum altitude 4000 ft under ATC clearance and missed approach. (3) GNSS required. (4) GNSS or (DME/DME) required; - DME GDV must be operational for (DME/DME). (5) GNSS or (DME/DME) required; - DME LPC must be operational for (DME/DME)									