

PAMPLONA
RNP Y
RWY 15



AIRAC AMDT 11/26

AERONAUTICAL DATABASE REQUIREMENTS

INSTRUMENT APPROACH PROCEDURES

RNP Y RWY 15

WAYPOINTS COORDINATES

WPT	COORD
DITOP (IAF)	430056.1N 0014551.7W
GOMSO (IAF)	425942.4N 0013000.0W
LEQIM (IAF)	424751.0N 0014948.0W
MALOB (IAF)	425041.8N 0015619.2W
PP06N (FAF LNAV)	425136.6N 0014243.6W
PP11N (IF)	425638.4N 0014624.5W
PP602	425252.0N 0015334.0W
PP603	425323.9N 0015317.6W
PP604	425551.7N 0015031.6W
PP610	425914.0N 0013952.0W
PP710	425517.0N 0013658.0W
PPN (IAF)	424401.5N 0014207.2W
RW15 (MAPt LNAV)	424646.4N 0013911.7W
Non-precision final approach (LNAV) - Slope (Descent angle)	5.64 % (3.23°)
APV Baro final approach (LNAV/VNAV) - Slope (Descent angle)	5.64 % (3.23°)

NOTES APPLICABLE TO ALL APPROACH:

- RNP APCH.

PROCEDURE TABULAR DESCRIPTION

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navigation specification
DITOP (IAF)											
001	IF	DITOP	-	-	-1.0	-	-	+FL065	-	-	RNP APCH
002	TF	PP11N	-	184 (185.3)	-1.0	4.3	-	+4700	-	-	RNP APCH
003	TF	PP06N	-	151 (151.7)	-1.0	5.7	-	+3400	-	-	RNP APCH
004	TF	RW15	Y	151 (151.7)	-1.0	5.5	-	+1517	-	-3.2/49	RNP APCH
005	DF	PP710	Y	-	-1.0	-	L	+4000	-185	-	RNP APCH
006	DF	LEQIM	-	-	-1.0	-	L	-	-210	-	RNP APCH

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navigation specification
GOMSO (IAF)											
001	IF	GOMSO	-	-	-1.0	-	-	+FL075	-	-	RNP APCH
002	TF	PP610	-	265 (266.3)	-1.0	7.3	-	+6000	-	-	RNP APCH
003	TF	PP11N	-	241 (241.7)	-1.0	5.5	-	+4700	-	-	RNP APCH
004	TF	PP06N	-	151 (151.7)	-1.0	5.7	-	+3400	-	-	RNP APCH

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navegation specification
005	TF	RW15	Y	151 (151.7)	-1.0	5.5	-	+1517	-	-3.2/49	RNP APCH
006	DF	PP710	Y	-	-1.0	-	L	+4000	-185	-	RNP APCH
007	DF	LEQIM	-	-	-1.0	-	L	-	-210	-	RNP APCH

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navegation specification
LEQIM (IAF)											
001	IF	LEQIM	-	-	-1.0	-	-	+6000	-	-	RNP APCH
002	TF	PP602	-	330 (331.1)	-1.0	5.7	-	+6000	-220	-	RNP APCH
003	TF	PP604	-	036 (036.7)	-1.0	3.7	-	+5500	-	-	RNP APCH
004	TF	PP11N	-	075 (075.6)	-1.0	3.1	-	+4700	-	-	RNP APCH
005	TF	PP06N	-	151 (151.7)	-1.0	5.7	-	+3400	-	-	RNP APCH
006	TF	RW15	Y	151 (151.7)	-1.0	5.5	-	+1517	-	-3.2/49	RNP APCH
007	DF	PP710	Y	-	-1.0	-	L	+4000	-185	-	RNP APCH
008	DF	LEQIM	-	-	-1.0	-	L	-	-210	-	RNP APCH

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navegation specification
MALOB (IAF)											
001	IF	MALOB	-	-	-1.0	-	-	+FL075	-220	-	RNP APCH
002	TF	PP603	-	038 (039.5)	-1.0	3.5	-	+FL065	-	-	RNP APCH
003	TF	PP604	-	039 (039.5)	-1.0	3.2	-	+5500	-	-	RNP APCH
004	TF	PP11N	-	075 (075.6)	-1.0	3.1	-	+4700	-	-	RNP APCH
005	TF	PP06N	-	151 (151.7)	-1.0	5.7	-	+3400	-	-	RNP APCH
006	TF	RW15	Y	151 (151.7)	-1.0	5.5	-	+1517	-	-3.2/49	RNP APCH
007	DF	PP710	Y	-	-1.0	-	L	+4000	-185	-	RNP APCH
008	DF	LEQIM	-	-	-1.0	-	L	-	-210	-	RNP APCH

Serial number	Path Terminator	Waypoint identifier	Fly-over	Course/Track °M (°T)	Magnetic variation	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	VPA/TCH (°/ft)	Navegation specification
PPN (IAF)											
001	IF	PPN	-	-	-1.0	-	-	+6000	-	-	RNP APCH
002	TF	LEQIM	-	303 (304.1)	-1.0	6.8	-	-	-	-	RNP APCH
003	TF	PP602	-	330 (331.1)	-1.0	5.7	-	+6000	-220	-	RNP APCH
004	TF	PP604	-	036 (036.7)	-1.0	3.7	-	+5500	-	-	RNP APCH
005	TF	PP11N	-	075 (075.6)	-1.0	3.1	-	+4700	-	-	RNP APCH
006	TF	PP06N	-	151 (151.7)	-1.0	5.7	-	+3400	-	-	RNP APCH
007	TF	RW15	Y	151 (151.7)	-1.0	5.5	-	+1517	-	-3.2/49	RNP APCH
008	DF	PP710	Y	-	-1.0	-	L	+4000	-185	-	RNP APCH
009	DF	LEQIM	-	-	-1.0	-	L	-	-210	-	RNP APCH

HOLDING PATTERN

Path terminator	Waypoint identifier	Course/Track °M (°T)	Magnetic variation	Distance/ Outbound time	Turn direction	MNM altitude (ft)	MAX altitude (ft)	Speed (kt)	Navigation specification
HM	PPN (1)	206 (207.0)	-1.0	1 MIN	R	6000	-	-185	RNAV1
HM	LEQIM (1)	271 (272.0)	-1.0	1 MIN	L	6000	-	-210	RNAV1
(1) RNAV 1									