


ELEV AD
1506 ft
VAR 1°E (2025)

PAMPLONA
LOC Y
RWY 15



CHANGES:



GS		kt		80		100		120		140		160		180	
FAF-THR:		min:s													
FAF-MAPT:		min:s		NO AUTORIZADO EL CRONOMETRAJE // TIMING NOT AUTHORISED											
ROD: 6.0%		ft/min		490		612		735		857		980		1102	
ALT/HGT DME (ILS) FNA															
13	12	11	10	9	8	7	6	5	4	3	2	1			
					4460 (2990)	4090 (2630)	3730 (2260)	3360 (1890)							

AERONAUTICAL DATABASE REQUIREMENTS

INSTRUMENT APPROACH PROCEDURES

LOC Y RWY 15

POINT	LAT	LONG	TRUE BEARING	DME DISTANCE (NM)
DVOR/DME PPN (IAF)	424401.7N	0014206.6W	–	–
L PP (IAF)	425159.9N	0014301.0W	–	–
FAF	425431.5N	0014451.6W	331.78° (LOC IPN)	8.80 DME ILS
MAPT	424739.2N	0013950.2W	331.78° (LOC IPN)	1.00 DME ILS
Non-precision final approach - Slope (Descent angle)				6.05% (3.46°)