

PAMPLONA
LOC Y
RWY 15



GS		kt	80	100	120	140	160	180
FAF-THR:		min:s						
FAF-MAPT:		min:s	NO AUTORIZADO EL CRONOMETRAJE // TIMING NOT AUTHORISED					
ROD: 6.0%		f/min	490	612	735	857	980	1102

ALT/HGT DME (ILS) FNA												
13	12	11	10	9	8	7	6	5	4	3	2	1
					4460 (2990)	4090 (2630)	3730 (2630)	3360 (1890)				



REQUISITOS DE LA BASE DE DATOS AERONÁUTICA

PROCEDIMIENTOS DE APROXIMACIÓN POR INSTRUMENTOS

LOC Y RWY 15

PUNTO	LAT	LONG	AZIMUT VERDADERO	DISTANCIA DME (NM)
DVOR/DME PPN (IAF)	424401.7N	0014206.6W	–	–
L PP (IAF)	425159.9N	0014301.0W	–	–
FAF	425431.5N	0014451.6W	331.78° (LOC IPN)	8.80 DME ILS
MAPT	424739.2N	0013950.2W	331.78° (LOC IPN)	1.00 DME ILS
Aproximación final de no precisión - Pendiente (Ángulo de descenso)				6.05% (3.46°)